



SPECIFICATIONS

- FLOW:-** 200 US GPM
- MICRON:-** 25 MICRON
- INLET SIZE:-** 3" 150# ANSI FLANGE
- OUTLET SIZE:-** 4" 150# ANSI FLANGE
- ELECTRICAL CONNECTION:-** 110VAC 1PH 60Hz
- CONSTRUCTION MATERIALS.**

- HOUSING:-** CARBON STEEL
- WHEELS:-** ALUMINUM
- SEALS:-** BUNA
- BELTING:-** 304 STAINLESS STEEL
- MEDIA BIN:-** (OPTIONAL) CARBON STEEL
- STAND:-** (OPTIONAL) CARBON STEEL

K Factor Filter. reserves all proprietary rights to this drawing and the data shown therein. This drawing is submitted in confidence and must not be used or reproduced without prior written consent or permission.	TOLERANCES UNLESS OTHERWISE NOTED DECIMALS 2 PLACE ± 0.015 DECIMALS 3 PLACE ± 0.005 DECIMALS 4 PLACE ± 0.0005 FRACTIONAL $\pm 1/32$ ANGLES $\pm 1^\circ$ DIM IN [] ARE mm REF. DEBURR ALL PARTS AND BREAK SHARP EDGES	DRAWN	NOV 2009	K FACTOR FILTER FILTRATION AT IT'S BEST		
		JFC DESIGNS				
THIRD ANGLE PROJECTION 	DO NOT SCALE DRAWING	Q.A.	-	TITLE:		
		MFG.	-	KW-200		
		APPROVAL	-	MATERIAL:-		
					FINISH:-	
				SIZE	MASS	DWG. NO.
				B	LBS	KW-200A01
		IF IN DOUBT-ASK		SCALE: 1:24		REV
				SHEET 1 OF 1		A